

Termofol TF-WIFI Thermostat

A modern thermostat used to control the heating– floor heating system. It is fitted with an internal air temperature sensor and a floor temperature sensor. It features a digital display and a touchscreen control panel. The thermostat is equipped with a Wi-Fi module. The heating system can be controlled via a smartphone app or the touchscreen panel.

Technical Specifications



WIFI

Supply voltage	230V AC 50/60 Hz
Power consumption	< 2 W
Sensors	internal (air), external NTC (floor)
Maximum load	16 A
Accuracy	±0,5 °C
Manufacturer's temperature range	5°C – 35°C
Programmable temperature range	1 – 70 °C
Hysteresis	0,5–2,5 °C
Hysteresis of the external sensor	1–9 °C
Modes	manual, automatic (programmable), holiday mode
Degree of protection	IP20
External dimensions	86 × 86 × 27 mm
Colours	white black
Installation instructions	flush-mounted, 60 mm or 86 mm can

Key features

- ▶ Wi-Fi control (TERMOFOL Smart, Tuya Smart)
- ▶ Programmable weekly timetable
- ▶ Manual, automatic and holiday modes
- ▶ Open window detection function
- ▶ Measuring energy consumption
- ▶ Overheating protection and key lock (Child Lock)

